21.2"

539mn

ON-ROAD

R-9715 Headliner

Air Conditioner

VAN • BUS • FIRE/RESCUE

The highest-capacity headliner A/C unit we make, the R-9715 is ideal for big interiors where appearance is important, including shuttle vehicles, buses, and fire trucks. An electric water pump can be used with tilt cabs or extremely humid conditions.





BTUs Cooling – 39,500 BTU/Hr with 36°F (11.6 kW with 2.2°C)

refrigerant temperature and 80°F (26.7°C) wet bulb entering air

AIR FLOW 577 CFM (980 m³/h)


WEIGHT 40 lbs. (18 Kg)

CURRENT 26.3 amps @ 13.6 VDC

DRAW (includes 4 amps for A/C clutch)

13.2 amps @ 27.2 VDC

(includes 2 amps for A/C clutch)



R-9715 SYSTEM ORDERING GUIDE			
	R-134a	NOTES	
UNITS	R-9715-11P R-9715-11-24P	12 VDC - replaces R-9715-10P 24 VDC - replaces R-9715-10-24P	
CONDENSER	R-4500-8P Remote Mount R-4500-8-24P Remote Mount	12 VDC 24 VDC	
INSTALLATION KIT	78R1070 78R1077	Rooftop condenser Rooftop condenser	ATCO version EZ Clip version
DUAL PUMP KIT	RD-2-3825-0P		
COMPRESSOR	Requires compressor and mounting kit		See 75 Series Compressor section on page 329